

No. of Core & Nominal Area of Conductor		Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor		Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor		Approx. O.D.	Approx. Weight	
			FR-200Q-M	FR-200C-M				FR-200Q-M	FR-200C-M				FR-200Q-M	FR-200C-M
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km			
1 X 10	rm	10.0	-	225	3 X 6	rm	15.7	430	445	10 X 1.0	rm	16.6	410	425
1 X 16	rm	11.4	-	290	3 X 10	rm	18.1	590	605	12 X 1.0	rm	18.0	455	470
1 X 25	cm	12.8	-	395	3 X 16	rm	20.9	845	860	16 X 1.0	rm	19.9	570	585
1 X 35	cm	14.5	-	550	3 X 25	cm	24.1	1230	1250	19 X 1.0	rm	21.3	640	655
1 X 50	cm	16.5	-	725	3 X 25	sm	22.8	1215	1230	24 X 1.0	rm	23.6	770	790
1 X 70	cm	18.5	-	970	3 X 35	cm	26.5	1600	1620	27 X 1.0	rm	24.1	830	850
1 X 95	cm	20.4	-	1260	3 X 35	sm	25.0	1530	1550	37 X 1.0	rm	28.8	1090	1105
1 X 120	cm	22.2	-	1525	3 X 50	cm	29.0	2040	2060	5 X 1.5	rm	14.2	315	325
1 X 150	cm	24.2	-	1830	3 X 50	sm	28.2	1965	1985	6 X 1.5	rm	15.4	350	360
1 X 185	cm	26.3	-	2270	3 X 70	sm	32.7	2730	2760	7 X 1.5	rm	15.4	375	385
1 X 240	rm	30.8	-	2910	3 X 95	sm	36.7	3630	3670	8 X 1.5	rm	16.6	430	440
1 X 300	rm	33.7	-	3530	3 X 120	sm	41.2	4470	4515	10 X 1.5	rm	18.2	510	525
2 X 1.0	rm	10.6	155	160	3 X 150	sm	44.8	5400	5460	12 X 1.5	rm	19.3	570	590
2 X 1.5	rm	11.2	170	175	4 X 1.0	rm	12.0	200	205	16 X 1.5	rm	21.4	760	780
2 X 2.5	rm	12.0	210	215	4 X 1.5	rm	12.6	240	245	19 X 1.5	rm	23.2	805	825
2 X 4	rm	13.7	290	300	4 X 2.5	rm	14.5	330	340	24 X 1.5	rm	25.5	975	995
2 X 6	rm	14.8	340	350	4 X 4	rm	15.5	400	415	27 X 1.5	rm	26.6	1050	1070
2 X 10	rm	17.0	470	485	4 X 6	rm	17.0	520	535	37 X 1.5	rm	30.3	1375	1400
2 X 16	rm	19.2	640	655	4 X 10	rm	19.7	740	755	5 X 2.5	rm	15.6	385	395
2 X 25	cm	22.0	925	940	4 X 16	rm	22.4	1070	1090	6 X 2.5	rm	17.2	445	460
2 X 25	sm	19.2	840	855	4 X 25	cm	26.1	1520	1540	7 X 2.5	rm	17.2	475	490
2 X 35	cm	24.6	1180	1200	4 X 25	sm	25.6	1490	1510	8 X 2.5	rm	18.2	530	540
2 X 35	sm	21.6	1085	1100	4 X 35	cm	29.3	1970	2000	10 X 2.5	rm	20.0	640	660
2 X 50	cm	27.9	1485	1520	4 X 35	sm	28.5	1960	1980	12 X 2.5	rm	21.4	725	745
2 X 50	sm	24.0	1400	1415	4 X 50	cm	34.2	2570	2600	16 X 2.5	rm	24.1	910	930
2 X 70	cm	33.2	2040	2060	4 X 50	sm	31.1	2560	2580	19 X 2.5	rm	25.8	1050	1070
2 X 70	sm	25.6	1900	1920	4 X 70	sm	35.9	3530	3570	24 X 2.5	rm	28.5	1275	1295
2 X 95	sm	28.4	2380	2400	4 X 95	sm	42.1	4670	4710	27 X 2.5	rm	29.8	1390	1410
2 X 120	sm	32.0	3120	3150	5 X 1.0	rm	12.8	225	235	37 X 2.5	rm	34.2	1840	1870
3 X 1.0	rm	11.2	170	175	6 X 1.0	rm	14.4	300	310	5 X 4	rm	17.2	510	525
3 X 1.5	rm	11.7	200	205	7 X 1.0	rm	14.4	310	320	6 X 4	rm	18.6	570	585
3 X 2.5	rm	12.8	245	250	8 X 1.0	rm	15.3	345	355	7 X 4	rm	18.6	615	630
3 X 4	rm	14.5	345	360										

rm : Stranded Circular Non-Compacted

cm : Stranded Circular Compacted

sm : Stranded Shaped

Note : * SST = Cables with lapped inner covering and a single sheath design.