

Number of Cores	Norminal Area of Conductor	No. and Diameter of Wires	Thickness of Insulation	Mean Overall Diameter Upper Limit	Approx. Weight	Minimum Insulation Resistance At 70°C
No.	mm ²	No. / mm	mm	mm	Kg / Km	Mohm - Km
1			H 0 5 V - K			
	0.5	16/0.20	0.6	2.5	10	0.013
	0.75	24/0.20	0.6	2.7	13	0.011
	1.0	32/0.20	0.6	2.8	15	0.010
			H 0 7 V - K			
	1.5	30/0.25	0.7	3.4	23	0.010
	2.5	50/0.25	0.8	4.1	35	0.0095
	4	56/0.30	0.8	4.8	51	0.0078
	6	84/0.30	0.8	5.3	71	0.0068
	10	80/0.40	1.0	6.8	120	0.0065
	16	126/0.40	1.0	8.1	180	0.0053
	25	196/0.40	1.2	10.2	280	0.0050
	35	276/0.40	1.2	11.7	380	0.0043
	50	396/0.40	1.4	13.9	540	0.0042
	70	360/0.50	1.4	16.0	760	0.0036
	95	475/0.50	1.6	18.2	1030	0.0036
	120	608/0.50	1.6	20.2	1280	0.0032
	150	756/0.50	1.8	22.5	1550	0.0032
	185	925/0.50	2.0	24.9	2000	0.0032
	240	1221/0.50	2.2	28.4	2500	0.0031