

No. of Cores	Nominal Area of Conductor	No. and Diameter of Wires	Thickness of Insulation	Thickness of Sheath	Mean O.D.		Approx. Weight	Minimum Insulation Resistance At 70°C
					Lower Limit	Upper Limit		
No.	mm ²	No. / mm	mm	mm	mm	mm	Kg / Km	Mohm - Km
2	0.5	16 / 0.20	0.6	0.8	5.4	6.8	58	0.013
	0.75	24 / 0.20	0.6	0.8	5.7	7.2	67	0.011
	1.0	32 / 0.20	0.6	0.8	5.9	7.5	77	0.010
	1.25	40 / 0.20	0.7	0.8	6.3	8.0	95	0.010
	1.5	30 / 0.25	0.7	0.8	6.8	8.6	103	0.010
	2.5	50 / 0.25	0.8	1.0	8.4	10.6	154	0.0095
	4	56 / 0.30	0.8	1.1	10.1	12.0	208	0.0078
3	0.75	24 / 0.20	0.6	0.8	6.0	7.6	79	0.011
	1.0	32 / 0.20	0.6	0.8	6.3	8.0	91	0.010
	1.25	40 / 0.20	0.7	0.9	6.9	8.7	117	0.010
	1.5	30 / 0.25	0.7	0.9	7.4	9.4	127	0.010
	2.5	50 / 0.25	0.8	1.0	9.2	11.4	183	0.0095
	4	56 / 0.30	0.8	1.2	11.0	13.0	260	0.0078
4	0.75	24 / 0.20	0.6	0.8	6.6	8.3	94	0.011
	1.0	32 / 0.20	0.6	0.9	7.1	9.0	114	0.010
	1.5	30 / 0.25	0.7	1.0	8.4	10.5	158	0.010
	2.5	50 / 0.25	0.8	1.1	10.1	12.5	232	0.0095
	4	56 / 0.30	0.8	1.2	12.0	14.0	318	0.0078
5	0.75	24 / 0.20	0.6	0.9	7.4	9.3	116	0.011
	1.0	32 / 0.20	0.6	0.9	7.8	9.8	133	0.010
	1.5	30 / 0.25	0.7	1.1	9.3	11.6	193	0.010
	2.5	50 / 0.25	0.8	1.2	11.2	13.9	282	0.0095
	4	56 / 0.30	0.8	1.4	13.5	15.5	396	0.0078