

Number of Cores	Nominal Area of Conductor	No. and Diameter of Wires	Thickness of Insulation	Thickness of Bedding	Thickness of Sheath	Approx. Overall Diameter	Approx. Weight
No.	mm ²	No. / mm	mm	mm	mm	mm	Kg / Km
2	1.5	30 / 0.25	0.7	0.8	1.8	11.8	194
	2.5	50 / 0.25	0.8	0.8	1.8	13.1	224
	4	56 / 0.30	0.8	0.8	1.8	14.2	310
	6	84 / 0.30	0.8	0.8	1.8	15.4	381
	10	80 / 0.40	1.0	0.8	1.8	18.2	553
	16	126 / 0.40	1.0	0.8	1.8	20.4	642
	25	196 / 0.40	1.2	1.0	1.8	24.3	940
	35	276 / 0.40	1.2	1.0	1.8	26.8	1185
	50	396 / 0.40	1.4	1.0	1.8	30.7	1580
3	1.5	30 / 0.25	0.7	0.8	1.8	12.3	220
	2.5	50 / 0.25	0.8	0.8	1.8	13.7	252
	4	56 / 0.30	0.8	0.8	1.8	14.9	364
	6	84 / 0.30	0.8	0.8	1.8	16.2	455
	10	80 / 0.40	1.0	0.8	1.8	19.2	674
	16	126 / 0.40	1.0	0.8	1.8	21.5	847
	25	196 / 0.40	1.2	1.0	1.8	25.7	1260
	35	276 / 0.40	1.2	1.0	1.8	28.4	1600
	50	396 / 0.40	1.4	1.0	1.8	32.6	2160
4	1.5	30 / 0.25	0.7	0.8	1.8	13.1	255
	2.5	50 / 0.25	0.8	0.8	1.8	14.6	290
	4	56 / 0.30	0.8	0.8	1.8	16.1	422
	6	84 / 0.30	0.8	0.8	1.8	17.4	542
	10	80 / 0.40	1.0	0.8	1.8	20.8	820
	16	126 / 0.40	1.0	1.0	1.8	24.0	1095
	25	196 / 0.40	1.2	1.0	1.8	28.0	1590
	35	276 / 0.40	1.2	1.0	1.8	31.2	2050
	50	396 / 0.40	1.4	1.2	1.9	36.4	2825