

Number of Cores	Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight
No.	mm <sup>2</sup>	mm	Kg / Km
2	1.5 rm	12.0	315
	2.5 rm	13.4	385
	4 rm	15.0	480
	6 rm	16.3	550
	10 rm	20.0	900
	16 rm	21.5	1120
	25 sm	22.0	1430
	35 sm	24.0	1610
	50 sm	27.0	2130
	70 sm	29.5	2470
3	1.5 rm	12.5	330
	2.5 rm	14.0	430
	4 rm	15.4	545
	6 rm	17.4	715
	10 rm	20.8	1000
	16 rm	22.5	1240
	25 sm	24.5	1700
	35 sm	26.6	2050
	50 sm	29.5	2550
	70 sm	33.0	3570
	95 sm	37.4	4590
	120 sm	40.4	5450
	150 sm	46.0	6880
	185 sm	50.0	8320
240 sm	55.0	10370	
300 sm	59.8	12480	
4	1.5 rm	13.5	370
	2.5 rm	14.5	465
	4 rm	17.0	730
	6 rm	18.8	840
	10 rm	22.2	1180
	16 rm	25.6	1570
	25 sm	26.6	2040
	35 sm	29.3	2550
	50 sm	34.0	3450
	70 sm	37.6	4480
	95 sm	43.0	5770
	120 sm	47.5	7400
	150 sm	51.5	8770
	185 sm	56.0	10630
240 sm	63.0	13300	
300 sm	68.5	16150	
400 sm	80.6	21600	
5 ( Colour )	1.5 rm	15.0	440
	2.5 rm	16.5	540
	4 rm	19.5	790
	6 rm	20.8	1030
	10 rm	25.8	1560
	16 rm	28.0	1990
	25 cm	32.1	2680
	35 cm	34.8	3330
	50 cm	41.0	4570
	70 cm	45.4	5830
5	1.5 rm	15.0	440
7		15.2	480
10		17.7	700
12		18.8	820
19		21.8	1110
27		26.0	1590
37		29.0	1960
5	2.5 rm	16.5	540
7		17.8	720
10		20.0	920
12		21.4	1090
19		26.0	1660
27		29.8	2120
37		33.5	2660
5	4 rm	19.5	790
7		20.2	870
10		24.4	1410
12		25.8	1560
19		30.2	2130
27		36.0	3040

rm : Stranded Circular Non-Compacted  
cm : Stranded Circular Compacted  
sm : Stranded Shaped

- Notes :
- The Bedding of cable sizes from 25 mm<sup>2</sup> and above are taped bedding.
  - For 7 cores & above Cables with earth core ( Green/Yellow ) are available upon request.
  - Any other cores ( up to 48 cores ) not indicated in this table are available upon request.