

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight	
		FRIM-200C-M	FRIM-200Q-M			FRIM-200C-M	FRIM-200Q-M			FRIM-200C-M	FRIM-200Q-M
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km
2 X 0.75	10.1	155	150	2 X 1.0	10.5	166	160	2 X 1.5	11.4	196	190
3 X 0.75	10.8	176	170	3 X 1.0	11.0	192	187	3 X 1.5	12.0	231	225
4 X 0.75	11.6	208	202	4 X 1.0	11.8	231	225	4 X 1.5	12.9	270	263
5 X 0.75	12.6	245	238	5 X 1.0	12.9	268	262	5 X 1.5	14.3	361	350
6 X 0.75	13.5	270	263	6 X 1.0	14.0	303	295	6 X 1.5	15.4	407	394
7 X 0.75	13.5	286	279	7 X 1.0	14.0	322	315	7 X 1.5	15.4	433	420
8 X 0.75	15.2	372	359	8 X 1.0	15.5	415	402	8 X 1.5	17.7	501	487
10 X 0.75	16.9	434	421	10 X 1.0	17.9	486	471	10 X 1.5	19.9	592	576
12 X 0.75	18.0	476	462	12 X 1.0	18.4	545	530	12 X 1.5	20.5	654	638
16 X 0.75	19.8	588	572	16 X 1.0	20.3	662	645	16 X 1.5	22.6	817	798
19 X 0.75	21.0	653	636	19 X 1.0	21.5	740	722	19 X 1.5	24.0	915	895
20 X 0.75	22.0	702	684	20 X 1.0	22.6	795	776	20 X 1.5	25.2	982	961
24 X 0.75	24.2	806	786	24 X 1.0	25.0	916	894	24 X 1.5	27.9	1153	1129
27 X 0.75	24.9	867	846	27 X 1.0	25.5	997	975	27 X 1.5	28.4	1242	1218
37 X 0.75	27.6	1094	1070	37 X 1.0	28.5	1251	1225	37 X 1.5	31.8	1589	1561

Note : * SST = Cables with lapped inner covering and a single sheath design.