

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight	
		FRIP-200C-M	FRIP-200Q-M			FRIP-200C-M	FRIP-200Q-M			FRIP-200C-M	FRIP-200Q-M
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km
2 X 2 X 0.75	16.9	299	290	2 X 2 X 1.0	17.7	333	324	2 X 2 X 1.5	19.7	444	428
3 X 2 X 0.75	18.0	361	351	3 X 2 X 1.0	18.8	402	391	3 X 2 X 1.5	20.9	530	512
4 X 2 X 0.75	20.0	480	464	4 X 2 X 1.0	21.0	540	523	4 X 2 X 1.5	22.9	642	623
6 X 2 X 0.75	23.7	645	625	6 X 2 X 1.0	25.0	728	707	6 X 2 X 1.5	27.2	868	845
7 X 2 X 0.75	23.7	687	667	7 X 2 X 1.0	25.0	782	760	7 X 2 X 1.5	27.2	933	910
8 X 2 X 0.75	26.2	784	762	8 X 2 X 1.0	26.8	873	851	8 X 2 X 1.5	28.7	1040	1015
10 X 2 X 0.75	28.0	917	893	10 X 2 X 1.0	29.5	1042	1017	10 X 2 X 1.5	31.6	1239	1212
12 X 2 X 0.75	30.3	1047	1022	12 X 2 X 1.0	31.9	1203	1175	12 X 2 X 1.5	34.4	1452	1422
14 X 2 X 0.75	32.3	1176	1147	14 X 2 X 1.0	34.2	1364	1334	14 X 2 X 1.5	36.6	1628	1596
16 X 2 X 0.75	34.3	1312	1282	16 X 2 X 1.0	36.2	1504	1472	16 X 2 X 1.5	38.9	1823	1789
19 X 2 X 0.75	36.9	1486	1454	19 X 2 X 1.0	39.1	1731	1697				

Note : * SST = Cables with lapped inner covering and a single sheath design.