

No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight
No. X mm ²	mm	Kg / Km	No. X mm ²	mm	Kg / Km	No. X mm ²	mm	Kg / Km
1 X 10	11.5	260	3 X 6	16.8	510	5 X 50	36.5	3200
1 X 16	12.7	360	3 X 10	19.2	710	5 X 70	42.0	4350
1 X 25	14.5	490	3 X 16	21.4	900	5 X 1.5	14.5	350
1 X 35	15.8	610	3 X 25 *	22.7	1220	6 X 1.5	16.0	400
1 X 50	17.2	765	3 X 35 *	23.9	1570	7 X 1.5	16.0	420
1 X 70	19.1	1030	3 X 50 *	26.7	2000	8 X 1.5	16.8	480
1 X 95	20.3	1325	3 X 70 *	30.5	2730	10 X 1.5	18.2	550
1 X 120	22.8	1620	3 X 95 *	35.2	3820	12 X 1.5	19.2	610
1 X 150	24.8	1940	3 X 120 *	39.8	4680	16 X 1.5	21.5	720
1 X 185	27.2	2400	3 X 150 *	42.1	5460	19 X 1.5	22.8	820
1 X 240	31.6	3040	4 X 1.5	13.5	300	24 X 1.5	25.0	970
1 X 300	33.0	3760	4 X 2.5	14.5	370	37 X 1.5	29.4	1330
2 X 1.5	11.9	240	4 X 4	16.5	460	5 X 2.5	16.0	410
2 X 2.5	13.0	290	4 X 6	17.7	600	6 X 2.5	17.1	460
2 X 4	14.2	370	4 X 10	20.5	840	7 X 2.5	17.1	490
2 X 6	16.0	440	4 X 16	23.2	1130	8 X 2.5	18.2	560
2 X 10	18.0	590	4 X 25 *	24.2	1540	10 X 2.5	19.9	670
2 X 16	20.2	790	4 X 35 *	26.9	1980	12 X 2.5	21.0	750
2 X 25 *	19.4	990	4 X 50 *	29.9	2600	16 X 2.5	23.2	910
2 X 35 *	20.2	1120	4 X 70 *	34.4	3540	19 X 2.5	24.9	1040
2 X 50 *	22.9	1430	4 X 95 *	38.6	4750	24 X 2.5	27.3	1240
2 X 70 *	25.9	1940	5 X 6	16.3	690	37 X 2.5	32.4	1750
2 X 95 *	29.2	2580	5 X 10	18.9	940	5 X 4	17.7	550
3 X 1.5	12.7	260	5 X 16	21.7	1280	6 X 4	19.2	630
3 X 2.5	13.6	320	5 X 25	25.2	1840	7 X 4	19.2	660
3 X 4	14.8	400	5 X 35	27.9	2400			